

Federal Communications Commission

§ 22.727

§ 22.723 Secondary site-by-site authorizations.

Authorizations for new facilities (including new sites and additional channel pairs for existing sites) in the Rural Radiotelephone Service (including BETRS facilities) may be granted after May 12, 1997 only on the condition that such authorizations shall be secondary to any existing or future co-channel paging geographic area authorization in the Paging and Radiotelephone Service or the Rural Radiotelephone Service. If the paging geographic area licensee notifies the Rural Radiotelephone Service licensee that operation of a co-channel secondary facility must be discontinued because it may cause interference to existing or planned facilities, the Rural Radiotelephone Service licensee must discontinue operation of that facility on the particular channel pair involved no later than six months after such notice.

[62 FR 11636, Mar. 12, 1997]

§ 22.725 Channels for conventional rural radiotelephone stations.

The following channels are allocated for paired assignment to transmitters that provide conventional rural radiotelephone service. These channels may be assigned for use by central office or rural subscriber stations as indicated, and interoffice stations. These channels may be assigned also for use by relay stations in systems where it would be impractical to provide rural radiotelephone service without the use of relay stations. All channels have a bandwidth of 20 kHz and are designated by their center frequencies in Mega-Hertz.

Central office	Rural subscriber	Central office	Rural subscriber
VHF Channels			
152.03	158.49	152.57	157.83
152.06	158.52	152.60	157.86
152.09	158.55	152.63	157.89
152.12	158.58	152.66	157.92
152.15	158.61	152.69	157.95
152.18	158.64	152.72	157.98
152.21	158.67	152.75	158.01
152.51	157.77	152.78	158.04
152.54	157.80	152.81	158.07

Central office	Rural subscriber	Central office	Rural subscriber
UHF Channels			
454.025	459.025	454.350	459.350
454.050	459.050	454.375	459.375
454.075	459.075	454.400	459.400
454.100	459.100	454.425	459.425
454.125	459.125	454.450	459.450
454.150	459.150	454.475	459.475
454.175	459.175	454.500	459.500
454.200	459.200	454.525	459.525
454.225	459.225	454.550	459.550
454.250	459.250	454.575	459.575
454.275	459.275	454.600	459.600
454.300	459.300	454.625	459.625
454.325	459.325	454.650	459.650

(a) The channels listed in this section are also allocated for assignment in the Paging and Radiotelephone Service.

(b) In Puerto Rico and the Virgin Islands, channels in the 154.04-154.46 MHz and 161.40-161.85 MHz frequency ranges may be assigned to transmitters providing rural radiotelephone service; channels in these ranges are also allocated for assignment in the International Fixed Public and Aeronautical Fixed radio services.

(c) In Alaska, channels 42.40, 44.10, 44.20 and 45.90 MHz are allocated for assignment to transmitters providing rural radiotelephone service using meteor burst propagation modes, subject to the provisions of § 22.729.

[59 FR 59507, Nov. 17, 1994; 60 FR 9891, Feb. 22, 1995]

§ 22.727 Power limits for conventional rural radiotelephone transmitters.

The transmitting power of transmitters operating on the channels listed in § 22.725 must not exceed the limits in this section.

(a) *Maximum ERP.* The effective radiated power (ERP) of central office and rural subscriber station transmitters must not exceed the applicable limits in this paragraph under any circumstances.

Frequency range (MHz)	Maximum ERP (watts)
152-153	1400
157-159	150
454-455	3500
459-460	150

(b) *Basic power limit.* Except as provided in paragraph (d) of this section,

§ 22.729

47 CFR Ch. I (10–1–03 Edition)

the ERP of central office station transmitters must not exceed 500 Watts.

(c) *Height-power limits.* Except as provided in paragraph (d) of this section, the ERP of central office station transmitters must not exceed the amount that would result in an average distance to the “service contour” of 41.6 kilometers (26 miles) for VHF channels or 30.7 kilometers (19 miles) for UHF channels. The average distance to the “service contour” is calculated by taking the arithmetic mean of the distances determined using the procedures specified in §22.567 for the eight cardinal radial directions, excluding cardinal radial directions for which 90% or more of the distance so calculated is over water.

(d) *Encompassed interfering contour areas.* Central office station transmitters are exempt from the basic power and height-power limits of this section if the area within their interfering contours is totally encompassed by the interfering contours of operating co-channel central office station transmitters controlled by the same licensee. For the purpose of this paragraph, operating transmitters are authorized transmitters that are providing service to subscribers.

(e) *Adjacent channel protection.* The ERP of central office station transmitters must not exceed 500 Watts if they transmit on channel 454.025 MHz and are located less than 7 kilometers (4.3 miles) from any Private Radio Services station receiving on adjacent channel 454.000 MHz.

(f) *Meteor burst stations.* The transmitter output power for stations using meteor burst propagation modes must not exceed 2000 Watts for central office stations and 500 Watts for rural subscriber stations.

§ 22.729 Meteor burst propagation modes.

The rules in this section govern stations in this service that use meteor burst propagation modes to provide rural radiotelephone service in Alaska.

(a) *Channel assignments.* The channels 42.40 and 44.10 MHz may be assigned to central office stations and rural subscriber stations, respectively, on a primary basis. The channels 44.20 and 45.90 MHz may be assigned to central office

and rural subscriber stations, respectively, on a secondary basis to Private Radio services stations using meteor burst propagation modes.

(b) *Transmitting power.* The transmitter output power must not exceed 2000 Watts for central office stations and 500 Watts for rural subscriber stations.

(c) *Station locations.* Co-channel central office stations of different licensees must be at least 241 kilometers (150 miles) apart. A rural subscriber station and a central office station of different licensees must be at least 241 kilometers (150 miles) apart if the rural subscriber stations of the different licensees operate on the same channel. The FCC may waive the requirements of this paragraph if the affected users agree to a cooperative sharing arrangement.

(d) *Emission type.* Only type F1D emission is authorized.

(e) *Bandwidth.* The authorized bandwidth is 20 kHz.

(f) *Station identification.* Station identification is required only for the central office station.

(g) *Interference.* Stations authorized under the provisions of this section must not cause harmful interference to the service of stations in other radio services.

(h) *Developmental authorization.* Meteor burst communications systems may be authorized under developmental authorizations pursuant to §22.419.

§ 22.731 Emission limitations.

Upon application for multichannel operation, the FCC may authorize emission bandwidths wider than those specified in §22.357, provided that spectrum utilization is equal to or better than that achieved by single channel operation.

§ 22.733 Priority of service.

Within the Rural Radiotelephone Service, the channels listed in §22.725 are intended primarily for use in rendition of public message service between rural subscriber and central office stations and to provide radio trunking facilities between central offices. The channels may also be used, however, for the rendition of private